

# **EMPOWER YOUR BUSINESS...**

## E BD ST 1000/6/38

## **BAUDOUIN Series Diesel Generator Sets**

STANDBY	kVA kW	1000 800
PRIME	kVA kW	909 727.2





Water Cooled

3 phase



60 hz





Diesel



Easy maintenance



Modular type soundproof canopy



Warning system for decreasing fuel with electronic fuel level sender



Remote control system

Emergency Standby Power: Emergency standby power, provided by diesel generators, acts as a backup during power outages. These generators kick in swiftly during emergencies, ensuring continuity for critical operations. Ideal for homes, businesses, and industries, their usage duration should be limited to prevent wear. Strict standards like NFPA 110 ensure their reliability.

**Prime Rated Power:** Prime rated power generators serve as primary power sources, especially in remote locations. These diesel generators handle varying loads over extended periods, making them perfect for sites without grid access. Commonly mobile, they're crucial for mining, construction, and energy industries, offering consistent, prime-rated power supply.

Continuous Operation Power: Continuous operation generators offer non-stop, stable power output, especially where grid access is inconsistent or expensive. These generators operate at a consistent 100% load, making them indispensable for remote mining, military, or farming sites. Unlike prime-rated generators, they don't vary in power, ensuring unwavering power delivery.

#### **QUALITY STANDARDS**

Our generators are manufactured in compliance with VDE 0530, BSE 4999 BS5000. IEC 34. EN12601: EN60204-1: TS ISO 8528-1 ... -13; EN12100-1; EN12100-2; EN61000-6-4; EN61000-6-2; EN61000-4-11; EN61000-4-6; EN61000-4-5; EN61000-4-2; EN55011; EN55016-2-1; EN55016-2-3; EN61000-3-2; EN61000-3-3; EN55014-1; EN61000-6-2; EN61000-4-3; EN61000-4-4; EN61000-4-8; EN61000-4-11; TS EN ISO 3744; TS EN ISO 3746; TS EN 60034-1; TS EN 60034-22; TS EN ISO 3046; BS 5514; NEMA MG 21; IEC 60034, BS 4999/5000 and TS EN 60947-1..4 standards.

We have ISO 9001-2015, ISO 14001-2015, ISO 45001-2018 and ISO 1002-2006 management system certificates from Kiwa, an accredited independent quality organization.

Our generators up to 400 kw are manufactured in compliance with 2000/14/EC European noise emission directive and certified from Ente Certificazione Macchine.

We also have TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 flame retardancy and TTS EN ISO 9227 certificates against anti-corrosion together with CE Declaration.













# **Engine Specifications**

- BAUDOUIN series heavy duty diesel engine
- 4 cycle, water cooling system, turbocharged aftercooler induction
- Electronic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe

12M26G800/6		
STANDBY kW	902	
PRIME kW	820	
	1800	
	4	
	31.8	
ERS	12 V	
	150 x 150	
)	15,7 : 1	
	STANDBY kW	

- Oil discharge valve and extention pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

GOVERNOR TYPE	Electronic		
Induction	TURBOCHARGED - AFTERCOOLER		
COMBUSTION SYSTEM	4	DIRECT	
Cooling System		WATER	
FUEL CONSUMPTION (lt/h)	100% OF PRIME POWER	203.1	
	75% OF PRIME POWER	151.8	
	50% OF PRIME POWER	105.6	
TOTAL LUBRICATION	SYSTEM CAPACITY	(lt) 114	
TOTAL COOLANT CAP	ACITY (It)	154	



# **Alternator Specifications**

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter

BRAND	STAMFORD
MODEL	S6L1D-D4
FREQUENCY (HZ)	60
POWER (KVA)	1004
DESIGN	4 pole, brushless
CONNECTION TYPE	Star
VOLTAGE (V)	380

- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid

Phase	3
A.V.R.	MX321
VOLTAGE REGULATION (+/-)	± 1%
INSULATION SYSTEM	Class H
PROTECTION	IP23
RATED POWER FACTOR	0.8
WEIGHT COMP. ALTERNATOR (KG)	1965



#### **Genset Controllers**



#### **Datakom SMART 500-MK2**

The SMART 500-MK2 is a cost effective genset controller ready for BMS integration and internet monitoring











#### **OPTIONAL GENSET CONTROLLERS OPTIONAL**

Datakom SMART 200

Datakom D500

Datakom D500-GSM

DEEPSEA 6120

DEEPSEA 7320

ComAp AMF25













	Datakom SMART 200	Datakom SMART 500-MK2	Datakom D500	Datakom D500 GSM	DEEPSEA 6120	DEEPSEA 7320	ComAp AMF25
AUTOMATIC MAINS MONITORING	✓	✓	✓	✓	✓	✓	✓
MANUEL START	✓	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	✓	<b>✓</b>
REMOTE START	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
REMOTE MONITORING WITH SIM CARD	OPTIONAL	OPTIONAL	OPTIONAL	1	×	OPTIONAL	OPTIONAL
1 ADITIONAL OPTION (HORN, OIL-FUEL HEATER ETC.)	×	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
LIGHT WARNING AND MIMIC DIAGRAM	✓	✓	✓	✓	✓	✓	✓
BATTERY CHARGER	✓	<b>✓</b>	<b>✓</b>	✓	<b>✓</b>	✓	✓
RS-485 COMMUNICATION	OPTIONAL	OPTIONAL	<b>✓</b>	<b>✓</b>	×	<b>√</b>	OPTIONAL
ETHERNET (TCP-IP) COMMUNICATION	×	<b>✓</b>	<b>✓</b>	<b>✓</b>	×	OPTIONAL	OPTIONAL

## GENSET CONTROLLERS FOR SYNCHRONIZATION SYSTEMS OPTIONAL

Next generation synchronizing genset controller capable of every communication and functionality.

DEEPSEA 8610



DEEPSEA 8620

DEEPSEA 8660



ComAp InteliGen BaseBox



ComAp InteliGen 200













### Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammeable acoustic foam
- Nano tech cleaning system
- Container optional

Emsa			EMSA .			
<u></u>	Dimensions (W x L x H) mm	1800x4800x2980 *	1	Dimensions (W x L x H) mm	1800x4140x2260	
<b>O</b> KG	Weight (Kg)	8681	KG	Weight (Kg)	7499	
	Fuel tank capacity (lt)	1450 Internal type		Fuel tank capacity (lt)	1450 Internal type	



#### External type

#### **SILENCER OPTIONS**

- Standard industrial type
- Critical type
- Hospital type

## **GEN-SET SAFETY PROTECTION & ALARMS**

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

Standard canopy

**CANOPY OPTIONS** 

- Super silent canopy
- Extra super silent canopy (thicker insulation)

#### **OPTIONAL EQUIPMENTS**

- Charge ammeter
- Moulded case circuit braker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile trailer
- Synchronization control panel for 2-16 gensets

- Over current load
- High & low genset voltage
- Start/stop failure
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water seperator filter
- PMG warning system







