

EMPOWER YOUR BUSINESS...

E IV MC 0110

FPT - IVECO Series Diesel Generator Sets

STANDBY	kVA kW	110 88
PRIME	kVA kW	100 80





Water Cooled



50 hz



Easy maintenance



Modular type soundproof canopy



3 phase



Diesel



Warning system for decreasing fuel with electronic fuel level sender



Remote control system

Emergency Standby Power: Emergency standby power, provided by diesel generators, acts as a backup during power outages. These generators kick in swiftly during emergencies, ensuring continuity for critical operations. Ideal for homes, businesses, and industries, their usage duration should be limited to prevent wear. Strict standards like NFPA 110 ensure their reliability.

Prime Rated Power: Prime rated power generators serve as primary power sources, especially in remote locations. These diesel generators handle varying loads over extended periods, making them perfect for sites without grid access. Commonly mobile, they're crucial for mining, construction, and energy industries, offering consistent, prime-rated power supply.

Continuous Operation Power: Continuous operation generators offer non-stop, stable power output, especially where grid access is inconsistent or expensive. These generators operate at a consistent 100% load, making them indispensable for remote mining, military, or farming sites. Unlike prime-rated generators, they don't vary in power, ensuring unwavering power delivery.

QUALITY STANDARDS

Our generators are manufactured in compliance with VDE 0530, BSE 4999 BS5000, IEC 34, EN12601; EN60204-1; TS ISO 8528-1 ... -13; EN12100-1; EN12100-2; EN61000-6-4; EN61000-6-2; EN61000-4-11; EN61000-4-6; EN61000-4-5; EN61000-4-2; EN55011; EN55016-2-1; EN55016-2-3; EN61000-3-2; EN61000-3-3; EN55014-1; EN61000-6-2; EN61000-4-3; EN61000-4-4; EN61000-4-8; EN61000-4-11; TS EN ISO 3744; TS EN ISO 3746; TS EN 60034-1; TS EN 60034-22; TS EN ISO 3046; BS 5514; NEMA MG 21; IEC 60034, BS 4999/5000 and TS EN 60947-1..4 standards.

We have ISO 9001-2015, ISO 14001-2015, ISO 45001-2018 and ISO 1002-2006 management system certificates from Kiwa, an accredited independent quality organization.

Our generators up to 400 kw are manufactured in compliance with 2000/14/EC European noise emission directive and certified from Ente Certificazione Macchine.

We also have TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 flame retardancy and TTS EN ISO 9227 certificates against anti-corrosion together with CE Declaration.















Engine Specifications

- FPT IVECO series heavy duty diesel engine
- 4 cycle, water cooling system, turbocharged aftercooler induction
- Mechanic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe

NEF45TM2A.S500		
STANDBY kW	96.2	
PRIME kW	89.6	
	1500	
	4	
	4.5	
ERS	4, in line	
	104 x 132	
0	17,5 : 1	
	STANDBY kW PRIME kW	

- Oil discharge valve and extention pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

GOVERNOR TYPE	Med	chanic	
Induction	TURBOCHARGED - AFTERCOOLER		
COMBUSTION SYSTEM	4	DIRECT	
Cooling System		WATER	
FUEL CONSUMPTION (lt/h)	100% OF PRIME POWER	22	
	75% OF PRIME POWER	16.2	
	50% OF PRIME POWER	11	
TOTAL LUBRICATION	SYSTEM CAPACITY (I	t) 12.8	
TOTAL COOLANT CAP	ACITY (It)	18.5	



Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter

BRAND	MECC ALTE
MODEL	ECP34-2S/4
FREQUENCY (HZ)	50
POWER (KVA)	110
DESIGN	4 pole, brushless
CONNECTION TYPE	Star
VOLTAGE (V)	400

- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid

Phase	3
A.V.R.	DSR
VOLTAGE REGULATION (+/-)	± 1%
INSULATION SYSTEM	Class H
PROTECTION	IP21
RATED POWER FACTOR	0.8
WEIGHT COMP. ALTERNATOR (KG)	419



Genset Controllers



Datakom SMART 500-MK2

The SMART 500-MK2 is a cost effective genset controller ready for BMS integration and internet monitoring











OPTIONAL GENSET CONTROLLERS OPTIONAL

Datakom SMART 200

Datakom D500

Datakom D500-GSM

DEEPSEA 6120

DEEPSEA 7320

ComAp AMF25













	Datakom SMART 200	Datakom SMART 500-MK2	Datakom D500	Datakom D500 GSM	DEEPSEA 6120	DEEPSEA 7320	ComAp AMF25
AUTOMATIC MAINS MONITORING	✓	✓	✓	✓	✓	✓	✓
MANUEL START	✓	✓	✓	✓	✓	✓	✓
REMOTE START	✓	1	1	1	1	✓	✓
REMOTE MONITORING WITH SIM CARD	OPTIONAL	OPTIONAL	OPTIONAL	✓	×	OPTIONAL	OPTIONAL
1 ADITIONAL OPTION (HORN, OIL-FUEL HEATER ETC.)	×	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
LIGHT WARNING AND MIMIC DIAGRAM	✓	✓	✓	✓	✓	✓	✓
BATTERY CHARGER	✓	✓	✓	✓	✓	✓	✓
RS-485 COMMUNICATION	OPTIONAL	OPTIONAL	✓	✓	×	✓	OPTIONAL
ETHERNET (TCP-IP) COMMUNICATION	×	1	1	1	×	OPTIONAL	OPTIONAL

GENSET CONTROLLERS FOR SYNCHRONIZATION SYSTEMS OPTIONAL

Next generation synchronizing genset controller capable of every communication and functionality.

DEEPSEA 8610





ComAp InteliGen BaseBox



ComAp InteliGen 200















Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammeable acoustic foam
- Nano tech cleaning system
- Container optional

- ems						
<u></u>	Dimensions (W x L x H) mm	1100x3220x1845		Dimensions (W x L x H) mm	1100x2600x1632	
KG	Weight (Kg)	1491	KG	Weight (Kg)	1185	
	Fuel tank capacity (It)	272 Internal type		Fuel tank capacity (lt)	272 Internal type	

SILENCER OPTIONS

- Standard industrial type
- Critical type
- Hospital type

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

OPTIONAL EQUIPMENTS

- Charge ammeter
- Moulded case circuit braker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile trailer
- Synchronization control panel for 2-16 gensets

CANOPY OPTIONS

- Standard canopy
- Super silent canopy
- Extra super silent canopy (thicker insulation)
- Over current load
- High & low genset voltage
- Start/stop failure
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water seperator filter
- PMG warning system







